SPIDERTM 125 WITH UNIVERSAL CLAMPING

Socket Tooling for 63mm to 125mm polypropylene pipe



OVERVIEW

The Spider[™] 125 with Universal Clamping system is the preferred equipment for quick and accurate socket fusion field installations of 63mm to 125mm polypropylene pipe.


The lightweight, compact device features a worm gear drive with parallel link system to bring pipe and fittings together evenly and under control. It features a Universal Clamping system that can accommodate any size of pipe or coupling, eliminating the need for inserts.


The features of the Spider 125 allow a single technician to properly align, heat, fuse and cool the pipe. Because the Spider is non back-drivable, constant pressure is maintained throughout the process.


The Spider has proven to be an exceptional tool for performing socket fusions in overhead, vertical and tight work spaces. A full assortment of heaters and heater adapters are available from McElroy for pipe sizes in the 63mm to 125mm range.


SPECIFICATIONS

CAPACITY	
Fuses Pipe Sizes:	63mm - 125mr
MODEL	
A456501:	Socket Tool with Universal Clamping Packag
WEIGHT	
Machine:	15 lbs. (6.8 Kg
MAXIMUM STROKE	
Length:	7.6 in. (193mn
MECHANICAL ADVANTAG	AE .
Ratio:	20-to-









SPIDER 125 with UNIVERSAL CLAMPING

INCLUSIONS

Package includes Spider fusion machine and carrying case. Heater and other socket fusion tooling sold separately. Specifications subject to change without notice.

FEATURES

- · Hand-powered
- · No inserts necessary
- · Universal Clamping jaw system fits all pipe brands and fittings
- · Non back-drivable gearing, self-locking
- Two-position support handle
- Lightweight and compact
- Self-centering
- Wide jaws provide stability on pipe

